

KENWOOD

NX-3720HG/3820HG

NEXEDGE®

NEXEDGE® VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG MOBILE RADIOS

NXDN® **DMR** **Gen2** **Bluetooth®** **GPS** **FleetSync®**

The adaptable mobile radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation critical applications. Designed with flexibility in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. And providing greater freedom of installation, the radio's front panel can be used as a remote control head (this requires an optional upgrade, to be available in the future). Additionally, for expansion capability a software license certification system facilitates extensive customization.

● FEATURE HIGHLIGHTS

- **Multi-protocol digital** radio: Designed to operate NXDN or DMR digital, and FM analog protocols
- **NXDN®** Conventional and Type-C & Gen2 Trunking
- **DMR Tier II & Site Roaming**
- **Mixed Digital & FM Analog Operation** allows gradual migration at your own pace
- **4-Line Basic Frame** (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- **4-Line Text Message Frame** (2 Lines of Text, icon & key guide) Note: The number of lines may vary depending on the display language (character set).
- **7-color LED** indicator
- External and Internal Speaker Switching
- **Built-In GPS Receiver** for effective fleet management
- **Built-in Bluetooth®** for hands-free operation - Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option; availability depends on the model)
- Renowned **KENWOOD Audio Quality** can be achieved with **Active Noise Reduction (ANR)** that utilizes built-in DSP
- **Software DES and AES Encryptions** for NXDN Conventional/Trunking and DMR Conventional protocols
- **MIL-STD-810 C/D/E/F/G**

● GENERAL FEATURES

- Audio Output Power (4 Watts at 4 ohms)
- 512 CH/128 Zones
- Maximum of 1000 CH/Radio with option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

● DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

● DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- ARC4 Encryption
- Energy Efficient

● ANALOG – FM MODES

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Options

<ul style="list-style-type: none"> KMC-9C Desktop Microphone KMC-59C Desktop Microphone <small>(Future Availability)</small> KMC-35 Microphone KMC-36 Keypad Microphone KES-3S External Speaker <small>(compact low profile; 3.5 mm plug)</small> 	<ul style="list-style-type: none"> KES-5 External Speaker <small>(40 W max input, requires KAP-2)</small> KCT-18 Ignition Sense Cable <small>(Requires KCT-60)</small> KCT-23 DC Power Cable <small>M: 10ft (3m) / M3: 23ft (7m)</small> 	<ul style="list-style-type: none"> KCT-60 Connection Cable <small>(D-sub 15 to Molex 15 Pin Connector)</small> KLF-2 Line Filter KMB-10 Key Lock Adapter KRA-40G GPS Active Antenna 	<ul style="list-style-type: none"> KPS-15 DC Power Supply <small>(23A max)</small> KMB-34 Mounting Case <small>for KPS-15</small> KPG-180AP OTAP Manager
---	--	---	--

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

GENERAL	NX-3720HG	NX-3820HG
Frequency Range	136-174 MHz	Type 1 450-520 MHz Type 2 400-470 MHz
Max. Channels Per Radio	Up to 1,000 CH with option	
Number of Channels	512	
Number of Zones	128	
Channel Spacing		
Analog	12.5/15/20/25*/30* kHz	12.5/25* kHz
Digital	6.25/12.5 kHz	6.25/12.5 kHz
Power Supply	13.6 V DC ±15%	
Current Drain		
Standby	0.45 A	
RX	2.3 A	
TX	12 A	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±1.0 ppm (-22°F to +140°F)	
Antenna Impedance	50 Ω	
Dimensions (W x H x D)	(W x H x D) Projections Not Included	
Radio w/Control Head	6.30 x 1.69 x 6.30 in (160 x 43 x 160 mm)	
Weight (net)	2.65 lbs (1.2 kg)	
FCC ID		
Type 1	K44479200	K44479300
Type 2	-	K44479301
IC Certification		
Type 1	282F-479200	-
Type 2	-	282F-479301

*25 and 30 kHz are not included in the models sold in the USA or US territories. Analog measurements made per EN Standards or TIA 603 and specifications shown are typical. Specifications are subject to change without notice, due to advancements in technology.

	NX-3720HG	NX-3820HG
RECEIVER		
Sensitivity		
NXDN® 6.25 kHz Digital (3% BER)		0.20 µV
NXDN® 12.5 kHz Digital (3% BER)		0.25 µV
DMR 12.5 kHz Digital (5% BER)		0.30 µV
DMR 12.5 kHz Digital (1% BER)		0.45 µV
Analog (12dB SINAD)		0.25 µV
Selectivity		
Analog @ 12.5 kHz		70 dB
Analog @ 25 kHz		80 dB
Intermodulation		70 dB
Spurious Rejection		80 dB
Audio Distortion		2 %
Audio Output Power		4 W/4 Ω
TRANSMITTER		
RF Power Output (High / Mid / Low)	50 W / 30 W / 5 W	45 W / 30 W / 5 W
Spurious Emission	-73 dB	-75 dB
FM Hum & Noise		
Analog @ 12.5 kHz		45 dB
Analog @ 25 kHz		40 dB
Audio Distortion		2 %
Digital Protocol	ETSI TS 102 361-1, -2, -3	
Emission Designator	16K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® is a registered trademark of JVCKENWOOD Corporation. FleetSync® is a registered trademark of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V
International Protection Standard					
Dust & Water*	IP54 (Radio unit itself)				

*Microphone KMC-35 or KMC-36 must be connected to the radio, and all accessory connectors must be covered.

KENWOOD

JVCKENWOOD USA Corporation
 Communications Sector Headquarters
 3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265
 Order Administration/Distribution
 P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
 Canadian Headquarters and Distribution
 6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
 JVCKENWOOD Corporation